

Mobrey 9700 Transmitter

Submersible Hydrostatic Level Transmitters



- Hydrostatic electronic level transmitters
- Factory sealed and tested for submersed duty
- 4–20 mA output signal proportional to level
- Flush mounted ceramic sensor
- Good long term stability
- Ideal for industrial or marine applications
- Wide range of mounting options
- Low cost installation
- Readouts for control room or plant mounting

Reliable Performance...In Challenging Applications

Mobrey 9700 Series transmitters

The 9700 Series range of tank level transmitters from Mobrey provide the measurement solution where in-tank problems such as foaming, vapor layers, and temperature gradients prohibit the use of other instrumentation.

The 9700 Series transmitter is designed to perform in the extreme conditions of today's industrial measurement applications.

Transmitters are available in both submersible and externally mounted (floodable) versions. Each transmitter version gives a high performance, has good long term stability, and is virtually maintenance free. A ceramic sensor ensures precise and reliable measurement with an accuracy of better than 0.1%.

Operation

At the heart is a Ceramic Capacitive Sensor (CCS). This pressure sensor provides a "flush" diaphragm, avoiding the risks of sensor clogging and ensures an extremely low hysteresis, minimal output drift, and high repeatability.

The sensor is manufactured using an aluminium oxide ceramic and provides outstanding resistance to chemical attack. The measuring range is determined by the ceramic thickness, which is precisely controlled during the manufacturing process. The sensor works like a capacitor with electrode surfaces on the inside comprising one measuring and one reference capacitor.

The surfaces of the capacitors are gold-plated and linked to ASIC electronics. These electronics generate a signal proportional to the applied pressure, which is sent to the 4–20 mA signal conditioner.



Mobrey 9710 Transmitter



Mobrey 9720 Transmitter



Mobrey 9780 Transmitter



Mobrey 9790 Transmitter

Contents

Mobrey 9700 Series transmitters	page 2	Mobrey 9790 Hydrostatic Level Transmitter Ordering	page 10
Mobrey 9710 Hydrostatic Level Transmitter Ordering ..	page 4	Specifications for 9710, 9720, 9780, and 9790	page 12
Mobrey 9720 Hydrostatic Level Transmitter Ordering ..	page 6	Product Certifications	page 13
Mobrey 9780 Hydrostatic Level Transmitter Ordering ..	page 8		

Features

- Two-wire 24 Vdc loop-powered
- 4 to 20 mA
- Accuracy $\pm 0.1\%$ of calibrated span
- Ranges up to 200 m / 656 ft. H₂O, and 10:1 rangeability
- Ceramic capacitive sensor
- Low maintenance
- Fully submersible IP68 / NEMA 6P
- Reverse polarity protection
- Dedicated marine version

Benefits

- Unaffected by difficult ullage conditions
- Stable readings under adverse conditions

Mounting options

The 9700 Series is available in various mounting configurations, all are rated IP68.

- 9710 – Cable suspended
- 9720 – Clamped, cable suspended
- 9780 – Pole mounted
- 9790 – Flanged

Bellows

For humid environments or sea water applications, bellows must be used (contact Delta Mobrey for details).

Mobrey 9710 Hydrostatic Level Transmitter Ordering

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment. See [page 12](#) for more information on Material Selections.

Table 1. Mobrey 9710 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

Model	Product Description		
9710	Cable Suspended Submersible Hydrostatic Level Transmitter		
Version			
Standard			Standard
C	Commercial		★
M	Marine approval		★
Material of Sensor			
Standard			Standard
S	Stainless steel 316		★
A	Aluminum bronze		★
Body Seal O-ring Material			
Standard			Standard
1	Fluorocarbon (FPM/FKM)		★
2	Nitrile		★
Nominal Range			
Standard			Standard
A	0 to 6.5 ft. (0 to 2 m) H ₂ O depth		★
B	0 to 16.4 ft. (0 to 5 m) H ₂ O depth		★
C	0 to 32.8 ft. (0 to 10 m) H ₂ O depth		★
D	0 to 65.6 ft. (0 to 20 m) H ₂ O depth		★
E	0 to 164 ft. (0 to 50 m) H ₂ O depth		★
F	0 to 328 ft. (0 to 100 m) H ₂ O depth		★
G	0 to 3.3 ft. (0 to 1 m) H ₂ O depth		★
H	0 to 11.5 ft. (0 to 3.5 m) H ₂ O depth		★
J	0 to 656 ft. (0 to 200 m) H ₂ O depth		★
Zero and Span			
Standard			Standard
1	Integral (fixed)		★
Cable Material			
Standard			Standard
P	Polyurethane		★
F	Fluorinated ethylene-propylene (F.E.P)		★
Cable Length Units			
Standard			Standard
E	English		★
M	Metric		★
Cable Length			Metric / English
Standard			Standard
003	3 meters	M	★
005	5 meters	M	★
008	8 meters	M	★
010	10 meters	M	★
020	20 meters	M	★
030	30 meters / feet	M / E	★
040	40 meters	M	★

Table 1. Mobrey 9710 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

050	50 meters	M	★
060	60 meters	M	★
075	75 meters	M	★
100	100 meters	M	★
125	125 meters	M	★
150	150 meters / feet	M / E	★
200	200 meters	M	★
009	9 feet	E	★
015	15 feet	E	★
024	24 feet	E	★
060	60 feet	E	★
090	90 feet	E	★
120	120 feet	E	★
225	225 feet	E	★
300	300 feet	E	★
375	375 feet	E	★
450	450 feet	E	★
600	600 feet	E	★
Product Certifications			
Standard			Standard
NA	Non-certified (non-hazardous area use only)		★
A6	CSA (Canada and USA)		★
Typical Model Number: 9710 C S 1 A 1 P M 003 NA			

Options (add to end of model number)

Custom Configuration		
Expanded		
C1	Custom configuration of actual range (customer to specify with order)	
Example Model Number: 9710 C S 1 A 1 P M 003 NA C1		

Mobrey 9720 Hydrostatic Level Transmitter Ordering

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment. See [page 12](#) for more information on Material Selections.

Table 2. Mobrey 9720 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

Model	Product Description		
9720	Clamped Cable Suspended Submersible Hydrostatic Level Transmitter		
Version			
Standard			Standard
C	Commercial		★
M	Marine approval		★
Material of Sensor			
Standard			Standard
S	Stainless steel 316		★
A	Aluminum bronze		★
Body Seal O-ring Material			
Standard			Standard
1	Fluorocarbon (FPM/FKM)		★
2	Nitrile		★
Nominal Range			
Standard			Standard
A	0 to 6.5 ft. (0 to 2 m) H ₂ O depth		★
B	0 to 16.4 ft. (0 to 5 m) H ₂ O depth		★
C	0 to 32.8 ft. (0 to 10 m) H ₂ O depth		★
D	0 to 65.6 ft. (0 to 20 m) H ₂ O depth		★
E	0 to 164 ft. (0 to 50 m) H ₂ O depth		★
F	0 to 328 ft. (0 to 100 m) H ₂ O depth		★
G	0 to 3.3 ft. (0 to 1 m) H ₂ O depth		★
H	0 to 11.5 ft. (0 to 3.5 m) H ₂ O depth		★
J	0 to 656 ft. (0 to 200 m) H ₂ O depth		★
Zero and Span			
Standard			Standard
1	Integral (fixed)		★
Cable Material			
Standard			Standard
P	Polyurethane		★
F	Fluorinated ethylene-propylene (F.E.P)		★
Cable Length Units			
Standard			Standard
E	English		★
M	Metric		★
Cable Length		Metric / English	
Standard			Standard
003	3 meters	M	★
005	5 meters	M	★
008	8 meters	M	★
010	10 meters	M	★
020	20 meters	M	★
030	30 meters / feet	M / E	★
040	40 meters	M	★
050	50 meters	M	★
060	60 meters	M	★
075	75 meters	M	★

Table 2. Mobrey 9720 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

100	100 meters	M	★
125	125 meters	M	★
150	150 meters / feet	M / E	★
200	200 meters	M	★
009	9 feet	E	★
015	15 feet	E	★
024	24 feet	E	★
060	60 feet	E	★
090	90 feet	E	★
120	120 feet	E	★
225	225 feet	E	★
300	300 feet	E	★
375	375 feet	E	★
450	450 feet	E	★
600	600 feet	E	★
Product Certifications			
Standard			Standard
NA	Non-certified (non-hazardous area use only)		★
A6	CSA (Canada and USA)		★
Typical Model Number: 9720 C S 1 A 1 P M 003 NA			

Options (add to end of model number)

Custom Configuration		
Expanded		
C1	Custom configuration of actual range (customer to specify with order)	
Example Model Number: 9720 C S 1 A 1 P M 003 NA C1		

Mobrey 9780 Hydrostatic Level Transmitter Ordering

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment. See [page 12](#) for more information on Material Selections.

Table 3. Mobrey 9780 ordering information

All Mobrey 9780 instruments are manufactured as made-to-order items. Contact Delta Mobrey for delivery lead times.

Model	Product Description	
9780	Pole Mounted Submersible Hydrostatic Level Transmitter	
Version		
C	Commercial	
M	Marine approval	
Material of Sensor and Pole		
S	Stainless steel 316	
A	Aluminum bronze	
Body Seal O-ring Material		
1	Fluorocarbon (FPM/FKM)	
2	Nitrile	
Nominal Range		
A	0 to 6.5 ft. (0 to 2 m) H ₂ O depth	
B	0 to 16.4 ft. (0 to 5 m) H ₂ O depth	
C	0 to 32.8 ft. (0 to 10 m) H ₂ O depth	
G	0 to 3.3 ft. (0 to 1 m) H ₂ O depth	
H	0 to 11.5 ft. (0 to 3.5 m) H ₂ O depth	
Zero and Span		
1	Integral (Fixed)	
Cable Material		
P	Polyurethane	
F	Fluorinated ethylene-propylene (F.E.P)	
Cable Length Units		
E	English	
M	Metric	
Cable Length		Metric / English
003	3 meters	M
005	5 meters	M
008	8 meters	M
010	10 meters	M
020	20 meters	M
030	30 meters / feet	M / E
040	40 meters	M
050	50 meters	M
060	60 meters	M
075	75 meters	M
100	100 meters	M
125	125 meters	M
150	150 meters / feet	M / E
200	200 meters	M
009	9 feet	E
015	15 feet	E
024	24 feet	E
060	60 feet	E
090	90 feet	E
120	120 feet	E

Table 3. Mobrey 9780 ordering information

All Mobrey 9780 instruments are manufactured as made-to-order items. Contact Delta Mobrey for delivery lead times.

225	225 feet	E	
300	300 feet	E	
375	375 feet	E	
450	450 feet	E	
600	600 feet	E	
Product Certifications			
NA	Non-certified (non-hazardous area use only)		
A6	CSA (Canada and USA)		
Process Connection			
B	Fixed flange, DN40 PN40 (DIN 2635)		
C	Fixed flange, DN50 PN40 (DIN 2635)		
D	Fixed flange, DN80 PN40 (DIN 2635)		
F	Fixed flange, 2-in. ASME B16.5 Class 150		
G	Fixed flange, 3-in. ASME B16.5 Class 150		
Overall Length Units			
E	English		
M	Metric		
Overall Length			
xxxx	mm or inches, depending on overall length units		
Typical Model Number: 9780 M S 1 C 1 P E 009 NA CE 300			

Options (add to end of model number)

Custom Configuration			
Expanded			
C1	Custom configuration of actual range (customer to specify with order)		
Example Model Number: 9780 M S 1 C 1 P E 009 NA CE 300 C1			

Mobrey 9790 Hydrostatic Level Transmitter Ordering

Specification and selection of product materials, options, or components must be made by the purchaser of the equipment. See [page 12](#) for more information on Material Selections.

Table 4. Mobrey 9790 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

Model	Product Description	
9790	Flange Mounted Submersible Hydrostatic Level Transmitter	
Version		
Standard		Standard
C	Commercial	★
M	Marine approval	★
Sensor and Flange Material		
Standard		Standard
S	Stainless steel 316	★
A	Aluminum bronze	★
Body Seal O-ring Material		
Standard		Standard
1	Fluorocarbon (FPM/FKM)	★
2	Nitrile	★
Nominal Range		
Standard		Standard
A	0 to 6.5 ft. (0 to 2 m) H ₂ O depth	★
B	0 to 16.4 ft. (0 to 5 m) H ₂ O depth	★
C	0 to 32.8 ft. (0 to 10 m) H ₂ O depth	★
D	0 to 65.6 ft. (0 to 20 m) H ₂ O depth	★
E	0 to 164 ft. (0 to 50 m) H ₂ O depth	★
F	0 to 328 ft. (0 to 100 m) H ₂ O depth	★
G	0 to 3.3 ft. (0 to 1 m) H ₂ O depth	★
H	0 to 11.5 ft. (0 to 3.5 m) H ₂ O depth	★
J	0 to 656 ft. (0 to 200 m) H ₂ O depth	★
Zero and Span		
Standard		Standard
1	Integral (Fixed)	★
Cable Material		
Standard		Standard
P	Polyurethane	★
F	Fluorinated ethylene-propylene (F.E.P)	★
Cable Length Units		
Standard		Standard
E	English	★
M	Metric	★
Cable Length		Metric / English
Standard		Standard
003	3 meters	M
005	5 meters	M
008	8 meters	M
010	10 meters	M
020	20 meters	M
030	30 meters / feet	M / E
040	40 meters	M

Table 4. Mobrey 9790 ordering information

★The Standard offering represents the most common options. The starred options (★) should be selected for best delivery. The Expanded offering is subject to additional delivery lead time.

050	50 meters	M	★
060	60 meters	M	★
075	75 meters	M	★
100	100 meters	M	★
125	125 meters	M	★
150	150 meters / feet	M / E	★
200	200 meters	M	★
009	9 feet	E	★
015	15 feet	E	★
024	24 feet	E	★
060	60 feet	E	★
090	90 feet	E	★
120	120 feet	E	★
225	225 feet	E	★
300	300 feet	E	★
375	375 feet	E	★
450	450 feet	E	★
600	600 feet	E	★
Product Certifications			
Standard			Standard
NA	Non-certified (non-hazardous area use only)		★
A6	CSA (Canada and USA)		★
Process Connection			
Standard			Standard
A	Slip-on flange, DN25 PN40 (DIN 2635)		★
B	Fixed flange, DN40 PN40 (DIN 2635)		★
C	Fixed flange, DN50 PN40 (DIN 2635)		★
D	Fixed flange, DN80 PN40 (DIN 2635)		★
E	Slip-on flange, 1-in. ASME B16.5 Class 150		★
F	Fixed flange, 2-in. ASME B16.5 Class 150		★
G	Fixed flange, 3-in. ASME B16.5 Class 150		★
Typical Model Number: 9790 M S 1 A 1 P E 009 NA F			

Options (add to end of model number)

Custom Configuration			
Expanded			
C1	Custom configuration of actual range (customer to specify with order)		
Example Model Number: 9790 M S 1 A 1 P E 009 NA FC1			

Specifications for 9710, 9720, 9780, and 9790

Functional

Output signal

Two-wire, 4–20 mA

Power supply

10 to 30 Vdc

Load resistance

$R=50 \times (\text{supply voltage} - 10V) \dot{U}$

Measuring range

Up to 200 m / 656 ft. H₂O

Overrange limit

5 x range up to a max 600 m / 1968 ft. H₂O

Span adjustment

+10 to +100% of Upper Range Limit (URL)

Process temperature limit

9710, 9720, 9780: -20 to +60 °C / -4 to +140 °F

9790: -20 to +90°C (80 °C Ex ia)

Ambient temp. limits

-20 to +60 °C

Humidity limits

0 to 100% RH when terminated using a remote bellows box (contact Delta Mobrey for details).

Hazardous area certification

See “Product Certifications” on page 13

Performance

Accuracy

±0.1% of calibrated span
(includes effects of linearity, hysteresis and repeatability)

Stability

± 0.1% Upper Range Limit (URL) per 6 months

Temperature effect

±0.015% Upper Range Limit (URL) per °C / °F
(over ambient temp. range)

Physical

Cable entry

Glanding system supplied with required length of vented cable

Materials selection

Delta Mobrey provides a variety of products with various product options and configurations including materials of construction that can be expected to perform well in a wide range of applications. The product information presented is intended as a guide for the purchaser to make an appropriate selection for the application. It is the purchaser's sole responsibility to make a careful analysis of all process parameters (such as all chemical components, temperature, pressure, flow rate, abrasives, contaminants, etc.), when specifying product, materials, options and components for the particular application.

Delta Mobrey is not in a position to evaluate or guarantee the compatibility of the process fluid or other process parameters with the product, options, configuration or materials of construction selected.

Wetted parts

Sensor

Ceramic

Sensor housing

316 Stainless steel, Aluminium bronze

Seal rings

Fluorocarbon (FPM/FKM), Nitrile

Cable

Polyurethane

Fluorinated Ethylene Polypropylene (FEP)

Pole (9780 only)

316 Stainless Steel pole supplied with 316 Stainless Steel

Housing option

Copper Nickel pole supplied Aluminium Bronze Housing option

Ingress protection

IP68 / NEMA 6P (200 m / 656 ft. H₂O)

Approximate weight

0.7 Kg / 1.54 lbs (sensor only)

Product Certifications

Hazardous area certification

CSA (Canada and USA)

CL I, Div 1, Groups C and D
CL II, Div 1, Groups E, F and G
CL III
Ex ia IIB T4
AEx ia IIB T4

Marine approvals

- Lloyds Register
- American Bureau of Shipping
- Korean Register
- Germanischer Lloyd
- DNV
- RINA